

PCLARIS

THE FIRST CHOICE OF MORE **AUSTRALIAN FARMERS**



THE LARGEST RANGE OF SIDE BY SIDE **VEHICLES IN AUSTRALIA**













"Is Mid Size Your Size"



MID-SIZE

QUAD BIKE



FULL-SIZE



Mid-Size means it's a little shorter and a little narrower than the full-sized 3-seat range, but that also means it's more nimble, more manageable and more manoeuvrable.



WATCH NOW

P#LARIS

GENUINE PARTS & ACCESSORIES

"GET MORE DONE"



FOR YOUR COMFORT, SAFETY & PROTECTION



Mark Larkham talks about Polaris Genuine Accessories.

SOME OF OUR MOST POPULAR ACCESSORIES

RANGER DIESEL HD EPS



- 1. Glass tip out screen #2889031
- 2. Bull bar and side rail kit #AUST548
- 3. Poly half door #2882559
- 4. Tip down Headache rack #2881531
- 5. Premium poly sport roof #2882912
- 6. Poly rear panel #2883773
- 7. Pro Armor 81cm single-row light bar #2884299

RANGER 570 HD EPS ADC



ACCESSORY IDEAS

- 1. Steel half doors #Aust510
- 2. Tip out front screen #2881784
- 3. Matte black six'r alloy rims #1521507-521
- 4. Pro Armor attack tyres #5415613
- 5. Canvas seat covers #P772q 6. Front brushguard #2879973
- 10. Rear brushguard #2879972
 - 3 11. Pro Armor 25cm dual row light bar #2882075

7. Polysport roof #2883236

9. Rear poly panel #2879812

8. Cargo max system #2882177

12. Work beacon led light #2883265



- 1. Premium poly sports roof #2882912
- 2. Tip out windscreen #2889013
- 3. Poly rear panel #2883773
- 4. Steel half doors #AUST508
- 5. Scrub bar and side rail kit #AUST555
- 6. Work beacon led light #2883265
- 7. Ranger snorkel kit #AUST403

RANGER XP 1000 CREW NORTHSTAR



ACCESSORY IDEAS

- 1. Crew Poly sports roof #2883274
- 2. Full glass windshield #2889030
- 3. Windshield wiper kit #2883974
- 4. 76cm Pro Armor dual row light bar #2882074
- 5. 25cm Rear-facing Rigid light bar #2883123
- 6. Crew Rock guard with step #2883398

- 7. Poly front doors #2882561 8. Poly rear doors #2883437
- 9. 2,041kg Pro heavy duty winch #2882711
- 10. Front hood storage rack #2882690
- 11. Rear cargo max system #2882177

2023 MODEL LINE UP







IRS WITH

25.4CM OF

TRAVEL

DUMP BOX

227KG





ON DEMAND TRUE TURF MODE

ALL-WHEEL-DRIVE

(AWD)

25.4CM OF

TRAVEL

CAPACITY -

454KG

(AWD)



ON DEMAND VERSATRAC

TURF MODE

TRUE

ALL-WHEEL-

DRIVE (AWD)



HIGH PERFORMANCE VERSATRAC HANDBRAKE

454KG

ON DEMAND TRUE TURF MODE

ALL-WHEEL-DRIVE



DRIVE (AWD)

2023 MODEL LINE UP





XP KINETIC PREMIUM







ALL-WHEEL-DRIVE







LITHIUM ION BATTERY 14.9 KWH NOMINAL



XP KINETIC ULTIMATE







ALL-WHEEL-DRIVE





LITHIUM ION BATTERY BATTERY 29.8 KWH CHARGER NOMINAL



SP 570 NORTHSTAR








TRUE

ALL-WHEEL-

DRIVE (AWD)







HEATER & DEFROST WINCH















DRIVE (AWD)

VERSATRAC HEATER, A/C HIGH PERFORMANCE TURF MODE & DEFROST ON DEMAND TRUE ALL-WHEEL-

RANGER

CREW XP 1000 NORTHSTAR PREMIUM

POLARIS PRO HD 4,500 LB. WINCH



CREW SP 570 PREMIUM







DRIVE (AWD)







IRS WITH DUMP BOX 25.4CM CAPACITY -OF TRAVEL 227KG









ALL-WHEEL-







DUMP BOX CAPACITY -454KG









ALI-WHEEL

PERFORMANCE TURF MODE



VERSATRAC



IRS WITH

27.9CM

OF TRAVEL



DUMP BOX

CAPACITY

- 227 KG











ALL-WHEEL-

VERSATRAC HEATER, A/C POLARIS PRO PERFORMANCE TURF MODE & DEFROST HD 4,500 LB. WINCH

POLARIS RANGER SPECS S FEATURES



USING YOUR SXS VEHICLE

SAFELY

A message from Polaris about how to use your SxS vehicle safely.

Polaris has engineered the most capable utility and recreational off-road vehicles packed with safety technology such as Engineered Roll Over Protection (ROPS) Roll Cages, Active Decent Control (ADC), True On Demand All Wheel Drive and more. However when operating a side by side vehicle off-road, the Driver/User and passengers must ensure that they operate the vehicle safely. Here are a few Tips and Hints on how to enjoy your Side by side vehicle safely.

TIPS



Always wear a seat belt.

Most injuries occur from passengers or limbs being ejected from the vehicle during an accident. Seat belts are your best friend.



An appropriate helmet is recommended for all occupants (Driver & Passengers). The more passengers in a vehicle, the more likelihood of "head to head" impacts.







- Be aware of HIGH RISK situations such as sloping and hilly Terrain.
- Slow is best when navigating hilly or obstructed terrain.
- In these higher risk situations always use LOW RANGE.

 Overloading – Your Polaris is designed to carry a certain maximum load (which varies from model to model). Never exceed the maximum load and remember a loaded vehicle may handle and respond differently to an empty vehicle.



Be aware of your vehicle condition.
In particular it is a good habit throughout
your driving day to visually check that your
tyres are correctly inflated and you have
not picked up a puncture or have a partially
inflated tyre. Correct tyre pressures are
important for traction and handling.

ALWAYS WEAR A HELMET, SEAT BELT AND USE SAFETY NETS OR DOORS FOR YOUR PROTECTION









Helmet

Seat Belt

Safety Nets

Doors

















RANGER SP 530

RANGER 570 HD EPS ADC

RANGER SP 570 PREMIUM

RANGER SP 570 NORTHSTAR

Engine Type	4-Stroke Single Cylinder DOHC	4-Stroke Single Cylinder DOHC	4-Stroke Single Cylinder DOHC	4-Stroke Single Cylinder DOHC
Displacement	4-Stroke single cylinder bonc 567cc	4-Stroke Single Cylinder Dono	4-Stroke Shigle Cylinder bunc 567cc	567cc
Fuel System / Battery	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection
Cooling	Liquid	Liquid	Liquid	Liquid
Transmission/	·	· · · · · · · · · · · · · · · · · · ·	<u>. </u>	· · · · · · · · · · · · · · · · · · ·
Final Drive	Automatic PVT H/L/N/R/P; Shaft	Automatic PVT H/L/N/R/P; Shaft	Automatic PVT H/L/N/R/P; Shaft	Automatic PVT H/L/N/R/P; Shaft
Drive System	On-Demand True AWD/2WD/VersaTrac Turf Mode	On-Demand True AWD/2WD/VersaTrac Turf Mode	On-Demand True AWD/2WD/VersaTrac Turf Mode	On-Demand True AWD/2WD/VersaTrac Turf Mode
Engine Braking System / Active Descent Control	Not Equipped / Not Equipped	ADC Equipped	Not Equipped/Not Equipped	Not Equipped/Not Equipped
Front Suspension	MacPherson Strut 22.9 cm Travel	MacPherson Strut 22.9 cm Travel	MacPherson Strut 22.9 cm Travel	MacPherson Strut 22.9 cm Travel
Rear Suspension	Dual A-Arm, IRS 25.4 cm Travel	Dual A-Arm, IRS 25.4 cm Travel	Dual A-Arm, IRS 25.4 cm Travel	Dual A-Arm, IRS 25.4 cm Travel
Front/Rear Brakes	4-Wheel Hydraulic Disc	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers	4-Wheel Hydraulic Disc	4-Wheel Hydraulic Disc
Parking Brake	Park in Transmission	Park in Transmission	Park in Transmission	Park in Transmission
Front Tyres	25 x 8-12; Carlisle 489	25 x 8-12; Carlisle 489	25 x 8-12; Carlisle 489	25 x 8-12; Carlisle Terra Cross
Rear Tyres	25 x 10-12; Carlisle 489	25 x 10-12; Carlisle 489	25 x 10-12; Carlisle 489	25 x10-12; Carlisle Terra Cross
Wheels	Stamped Steel	Stamped Steel	12" Black Aluminum	12" Black Aluminum
Wheelbase	185.4 cm	200.7 cm	185.4 cm	185.4 cm
Dry Weight	525 kg	486 kg	564 kg	670 kg
Overall Vehicle Size (L x W x H)	274.3 x 142.2 x 188 cm	290 x 152 x 188 cm	274.3 x 142.2 x 188 cm	274.3 x 147.3 x 188 cm
Ground Clearance	27.9 cm	26.7 cm	27.9 cm	26.7 cm
Seating Capacity	2	3	2	2
Fuel Capacity	35.9 L	34.1 L	35.9 L	35.9 L
Bed Box Dimensions (L x W x H)	84.6 x 123.7 x 31.2 cm	93 x 137 x 29 cm	84.6 x 123.7 x 31.2 cm	84.6 x 123.7 x 31.2 cm
Front/Rear Rack or Box Capacity _	N.A / 227 kg	N.A / 363 kg	N.A / 227 kg	N.A / 227 kg
Payload Capacity	453 kg	680 kg	420 kg	318 kg
Hitch Towing Rating	680 kg	680 kg	680 kg	680 kg
Hitch Type	Standard 5 cm Receiver	Standard 5 cm Receiver	Standard 5 cm Receiver	Standard 5 cm Receiver
Cargo System/Cab	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride
Lighting	55W Headlight, LED Taillamps	50W Headlight, LED Taillight	High/Low Beam LED Headlights LED Taillamps	Halogen Headlamps, 55W low beam, 60W high beam, LED Taillamps
Electronic Power Steering	Not Equipped	Standard	Standard	Standard
Adjustable Driver's Seat	Not Equipped	Not Equipped	Not Equipped	Not Equipped
Tilt Steering	Standard	Standard	Standard	Standard
Instrumentation	4* LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder, DC Outlet	Single Analog Dial with 2° LCD Rider Information Center: Speedometer, Tachometer, Ddometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seatbelt Reminder Light, DC Outlet	4° LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder, DC Outlet	4° LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brigh Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmete Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service I and Codes, Seat Belt Reminder, DC Outlet
Other Standard Features	Gas Assist Dump Box, Single Latch Tailgate, Rear-mounted Fiberglass Insulated Exhaust System, Standard In-dash SAE Charge Port, 340 CCA Battery, 660W Charging System (Stator)	N.A	Gas Assist Dump Box, Single Latch Tailgate, Rear-mounted Fiberglass Insulated Exhaust System, Standard In-dash SAE Charge Port, 575 CCA Battery, 660W Charging System (Stator)	All great features of SP 570 Premium plus: Polaris HD 3,500 Lb. Synthetic Rope Winch with A and In-Dash Switch, Premium Pro-Shield Cab, Doors with Crank Windows, Integrated Door

Sage Green









RANGER 1000 EPS

RANGER 1000 PREMIUM

RANGER XP 1000 HD EPS ADC

Bronson Rock Smoke

RANGER DIESEL HD EPS ADC

Sage Green

Engine Type	4-Stroke Twin Cylinder SOHC	4-Stroke Twin Cylinder SOHC	4-Stroke Twin Cylinder DOHC	Kubota 3-Cylinder Diesel
Displacement	999cc	999сс	999сс	898cc
Fuel System / Battery	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection	Mechanical Injection
Cooling	Liquid	Liquid	Liquid	Liquid
Transmission/ Final Drive	Automatic PVT H/L/N/R/P; Shaft	Automatic PVT H/L/N/R/P; Shaft	Automatic PVT H/L/N/R/P; Shaft	Automatic PVT H / L / N / R / P; Shaft
Drive System	High Performance On-Demand True AWD/2WD/VersaTrac Turf Mode	High Performance On-Demand True AWD/2WD/VersaTrac Turf Mode	High Performance On-Demand True AWD/2WD/VersaTrac Turf Mode	On-Demand True AWD/2WD/Versatrac Turf Mode
Engine Braking System / Active Descent Control	Not Equipped/Not Equipped	Not Equipped/ Not Equipped	Engine Breaking & ADC Equipped	ADC Equipped
Front Suspension	Dual A-Arm 25.4 cm Travel	Dual A-Arm 25.4 cm Travel	Dual A-Arm 27.9 cm Travel	Dual A-Arm with Stabilizer Bar 27.9 cm Travel
Rear Suspension	Dual A-Arm, IRS 25.4 cm Travel	Dual A-Arm, IRS 25.4 cm Travel	Dual A-Arm, IRS 27.9 cm Travel	Dual A-Arm IRS with Stabilizer Bar 27.9 cm Travel
Front/Rear Brakes	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers	Hydraulic Disc
Parking Brake	Park in Transmission	Park in Transmission	Park in Transmission	Hand-Actuated
Front Tyres	25 x 10-12; Carlisle 489	26 x 9-12; PXT 2.0	27 x 9-14; Pro Armor X-Terrain	27 x 9; R12
Rear Tyres	25 x 11-12; Carlisle 489	26 x 11-12; PXT 2.0	27 x 11-14; Pro Armor X-Terrain	27 x 11; R12
Wheels	Stamped Steel	Aluminum Black Xcelerator 2.0	14" Aluminum	12" Steel
Wheelbase	206 cm	206 cm	206 cm	206 cm
Dry Weight	674 kg	674 kg	737 kg	766 kg
Overall Vehicle Size (L x W x H)	305 x 158 x 193 cm	305 x 158 x 193 cm	305 x 158 x 196 cm	305 x 158 x 196 cm
Ground Clearance	30.5 cm	31.8 cm	33 cm	33 cm
Seating Capacity	3	3	3	3
Fuel Capacity	43 L	43 L	43.5 L	43.5 L
Bed Box Dimensions (L x W x H)	93.3 x 137.8 x 31.75 cm	93.3 x 137.8 x 31.75 cm	93.3 x 137.8 x 31.75 cm	93.3 x 137.8 x 31.75 cm
Front/Rear Rack or Box Capacity	N.A / 454 kg	N.A / 454 kg	N.A / 454 kg	N.A / 435 kg
Payload Capacity	680 kg	680 kg	680 kg	720 kg
Hitch Towing Rating	680 kg	1,134 kg	1,134 kg	1,134 kg
Hitch Type	Standard 5 cm Receiver	Standard 5 cm Receiver	Standard 5 cm Receiver	Receiver w/ ECE R55 ball
Cargo System/Cab	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride
Lighting	Halogen Headlamps, 55W Low Beam, 60W High Beam, Dual LED Taillamps	Dual LED Headlamps, 600lm Low Beam, 1000lm High Beam, Dual LED Taillamps	Dual LED Headlamps, 1250 lm Low Beam, 2300 lm High Beam, Dual LED Taillamps	Headlights : halogen
Electronic Power Steering	Standard	Standard	Standard	Standard
Adjustable Driver's Seat	Not Equipped	Standard	Standard	N.A
Tilt Steering	Standard	Standard	Standard	N.A
- Instrumentation	4° LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder, DC Outlet	4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder, DC Outlet	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Sauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder, 1 DC Outlet, 1 USB Charge Port	All Digital Gauge, Speedometer, Odometer, Tachometer, 2 Trip Meters, Hour M Gear Indicator, Fuel Gauge, Engine Temperature, Hi-Temp Light, Clock, Glow Indicator, Low Oil Pressure Indicator, Seat Belt Indicator, Parking Brake Enga Alarm, Horn, Backup Alarm
Other Standard Features	Polaris Pulse Electrical System (3 position), Standard In-Dash SAE Charge Port	Premium Cut & Sew Seats, Polaris Pulse Electrical System (3 position), Standard In-Dash SAE Charge Port	Premium Cut & Sew Seats with Contoured Seatbacks and Embroidered Polaris Branding, Premium Steering Wheel and Interior Accents	N.A







RANGER XP 1000 NORTHSTAR PREMIUM

RANGER XP KINETIC PREMIUM

RANGER XP KINETIC ULTIMATE

	Engine Type	4-Stroke Twin Cylinder DOHC	Interior Permanent Magnet AC Motor	Interior Permanent Magnet AC Motor
¥	Displacement 999cc Fuel System / Battery Electronic Fuel Injection		N.A	N.A
ENGINE			Lithium-lon, 14.9 kWh Nominal	Lithium-Ion, 29.8 kWh Nominal
	Cooling Liquid		Active Air and Liquid	Active Air and Liquid
-	Transmission/ Final Drive	Automatic PVT H/L/N/R/P; Shaft	Gates Synchronous Belt H/L/N/P (Electronic Forward/Reverse), Shaft	Gates Synchronous Belt H/L/N/P (Electronic Forward/Reverse), Shaft
TRAII	Drive System	High Performance On-Demand True AWD/2WD/VersaTrac Turf Mode	High Performance On-Demand True AWD/2WD/ VersaTrac Turf Mode	High Performance On-Demand True AWD/2WD/ VersaTrac Turf Mode
DRIVETRAIN	Engine Braking System / Active Descent Control	Not Equipped / Not Equipped	Regenerative Braking / Not Equipped	Regenerative Braking / Not Equipped
PEN-	Front Suspension	Dual A-Arm 27.9 cm Travel	Dual A-Arm 25.4 cm Travel	Dual A-Arm 25.4 cm Travel
SUS	Rear Suspension	Dual A-Arm, IRS 27.9 cm Travel	Dual A-Arm, IRS 25.4 cm Travel	Dual A-Arm, IRS 25.4 cm Travel
BRAKES	Front/Rear Brakes	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front Callipers	4-Wheel Hydraulic Disc with Dual-Bore Front Callipers
8	Parking Brake	Park in Transmission	Park In-Transmission	Park In-Transmission
SS SS	Front Tyres	27 x 9-14; Pro Armor X-Terrain	29 X 9-14; PRO ARMOR X-TERRAIN; 8-Ply Rated	29 X 9-14; PRO ARMOR X-TERRAIN; 8-Ply Rated
ESA	Rear Tyres	27 x 11-14; Pro Armor X-Terrain	$29\times1114;$ PRO ARMOR X-TERRAIN; 8-Ply Rated	29 x 11-14; PRO ARMOR X-TERRAIN; 8-Ply Rated
₹>	Wheels	35.6 cm Aluminum	35.6 cm Aluminum	14" Aluminum
	Wheelbase	206 cm	206 cm	206 cm
	Dry Weight	867 kg	785 kg – vehicle weight subject to change	900 kg – vehicle weight subject to change
s	Overall Vehicle Size (L x W x H)	305 x 165 x 198 cm	305 x 158 x 198 cm	305 x 158 x 198 cm
ij	Ground Clearance	33 cm	35.5 cm	35.5 cm
APAC	Seating Capacity	3	3	3
S/C	Fuel Capacity	43.5 L	N.A	N.A
DIMENSIONS / CAPACITIES	Bed Box Dimensions (L x W x H)	93.3 x 137.8 x 31.75 cm	93.3 x 137.8 x 31.75 cm	93.3 x 137.8 x 31.75 cm
DIME	Front/Rear Rack or Box Capacity	454 kg	N.A / 567 kg	N.A / 587 kg
	Payload Capacity			
<u></u>		578 kg	680 kg	680 kg
	Hitch Towing Rating	578 kg 1,134 kg	680 kg 1,134 kg	680 kg 1,134 kg
	Hitch Towing Rating Hitch Type			
		1,134 kg	1,134 kg	1,134 kg
	Hitch Type	1,134 kg Standard 5 cm Receiver	1,134 kg Standard 5 cm Receiver	1,134 kg Standard 5 cm Receiver
	Hitch Type Cargo System/Cab	1,134 kg Standard 5 cm Receiver Lock & Ride	1,134 kg Standard 5 cm Receiver Lock & Ride®	1,134 kg Standard 5 cm Receiver Lock & Ride®
	Hitch Type Cargo System/Cab Lighting	1,134 kg Standard 5 cm Receiver Lock & Ride Dual LED Headlamps, 1250lm Low Beam, 2300lm High Beam, Dual LED Taillamps	1,134 kg Standard 5 cm Receiver Lock & Ride® Dual LED Headlamps, 1250lm low beam, 2300lm high beam, LED Front Accent Light with Charge Indicator, Dual LED Taillamps	1,134 kg Standard 5 cm Receiver Lock & Ride® Dual LED Headlamps, 7250lm low beam, 2300lm high beam, LED Front Accent Light with Charge Indicator, Dual LED Taillamps
S	Hitch Type Cargo System/Cab Lighting Electronic Power Steering	1,134 kg Standard 5 cm Receiver Lock & Ride Dual LED Headlamps, 1250lm Low Beam, 2300lm High Beam, Dual LED Taillamps Standard	1.134 kg Standard 5 cm Receiver Lock & Ride® Dual LED Headlamps, 1250lm low beam, 2300lm high beam, LED Front Accent Light with Charge Indicator, Dual LED Taillamps Standard	1,134 kg Standard 5 cm Receiver Lock & Ride® Dual LED Headlamps, 1250lm low beam, 2300lm high beam, LED Front Accent Light with Charge Indicator, Dual LED Taillamps Standard
FEATURES	Hitch Type Cargo System/Cab Lighting Electronic Power Steering Adjustable Driver's Seat	1,134 kg Standard 5 cm Receiver Lock & Ride Dual LED Headlamps, 1250lm Low Beam, 2300lm High Beam, Dual LED Taillamps Standard Standard	1,134 kg Standard 5 cm Receiver Lock & Ride® Dual LED Headlamps, 1250lm low beam, 2300lm high beam, LED Front Accent Light with Charge Indicator, Dual LED Taillamps Standard Premium Cut & Sew Seats with Contoured Seatbacks and Embroidered Polaris Branding	1,134 kg Standard 5 cm Receiver Lock & Ride® Dual LED Headlamps, 1250lm low beam, 2300lm high beam, LED Front Accent Light with Charge Indicator, Dual LED Taillamps Standard Premium Cut & Sew Seats with Contoured Seatbacks and Embroidered Polaris Branding









RANGER CREW SP 570 PREMIUM

RANGER CREW 1000 PREMIUM

RANGER CREW XP 1000 PREMIUM

RANGER CREW XP 1000 NORTHSTAR PREMIUM

Engine Type	4-Stroke Single Cylinder DOHC	4-Stroke Twin Cylinder SOHC	4-Stroke Twin Cylinder DOHC	4-Stroke Twin Cylinder DOHC
Displacement	567cc	999cc	999cc	999cc
Fuel System / Battery	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection
Cooling	Liquid	Liquid	Liquid	Liquid
Transmission/ Final Drive	Automatic PVT H/L/N/R/P; Shaft	Automatic PVT H/L/N/R/P; Shaft	Automatic PVT H/L/N/R/P; Shaft	Automatic PVT H/L/N/R/P; Shaft
Drive System	On-Demand True AWD/2WD/VersaTrac Turf Mode	High Performance On-Demand True AWD/2WD/VersaTrac Turf Mode	High Performance On-Demand True AWD/2WD/VersaTrac Turf Mode	High Performance On-Demand True AWD/2WD/VersaTrac Turf Mode
Engine Braking System / Active Descent Control	Not Equipped / Not Equipped	Not Equipped / Not Equipped	Not Equipped / Not Equipped	Not Equipped / Not Equipped
Front Suspension	MacPherson Strut 22.9 cm Travel	Dual A-Arm 25.4 cm Travel	Dual A-Arm 27.9 cm Travel	Dual A-Arm 27.9 cm Travel
Rear Suspension	Dual A-Arm, IRS 25.4 cm Travel	Dual A-Arm, IRS 25.4 cm Travel	Dual A-Arm, IRS 27.9 cm Travel	Dual A-Arm, IRS 27.9 cm Travel
Front/Rear Brakes	4-Wheel Hydraulic Disc	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers
Parking Brake	Park in Transmission	Park in Transmission	Park in Transmission	Park in Transmission
Front Tyres	25 x 8-12; Carlisle 489	26 x 9-12; PXT 2.0	27 x 9-14; Pro Armor X-Terrain	27 x 9-14; Pro Armor X-Terrain
Rear Tyres	25 x 10-12; Carlisle 489	26 x 11-12; PXT 2.0	27 x 11-14; Pro Armor X-Terrain	27 x 11-14; Pro Armor X-Terrain
Wheels	12" Black Aluminum	Aluminum Black Xcelerator 2.0	35.6 cm Aluminum	35.6 cm Aluminum
Wheelbase	266.7 cm	287 cm	287 cm	287 cm
Dry Weight	703 kg	814 kg	859 kg	1,063 kg
Overall Vehicle Size (L x W x H)	365.8 x 142.2 x 188 cm	386 x 158 x 193 cm	386 x 158 x 196 cm	386 x 165 x 198 cm
Ground Clearance	27.9 cm	31.8 cm	33 cm	33 cm
Seating Capacity	4	6	6	6
Fuel Capacity	35.9 L	43 L	43.5 L	43.5
Bed Box Dimensions (L x W x H)	84.6 x 123.7 x 31.24 cm	93.3 x 137.8 x 31.75 cm	93.3 x 137.8 x 31.75 cm	93.3 x 137.8 x 31.75 cm
Front/Rear Rack or Box Capacity	N.A / 227 kg	N.A / 454 kg	454 kg	455 kg
Payload Capacity	499 kg	794 kg	767 kg	558 kg
Hitch Towing Rating	680 kg	1,134 kg	1,134 kg	1,134 kg
Hitch Type -	Standard 5 cm Receiver	Standard 5 cm Receiver	Standard 5 cm Receiver	Standard (5 cm Receiver
Cargo System/Cab	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride
Lighting	High/Low Beam LED Headlights LED Taillamps	Dual LED Headlamps, 600lm Low Beam, 1000lm High Beam, Dual LED Taillamps	Dual LED Headlamps 1250Im Low Beam 2300Im High Beam Dual LED Taillamps	Dual LED Headlamps, 1250lm Low Beam, 2300lm High Beam, Dual LED Tailla
Electronic Power Steering	Standard	Standard	Standard	Standard
Adjustable Driver's Seat	Not Equipped	Standard	Standard	Standard
Tilt Steering	Standard	Standard	Standard	Standard
Instrumentation	4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder, DC Outlet	4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder, DC Outlet	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/ Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder, 2 DC Outlets, 1 USB Charge Port	Dual-sweep Analog Dials w/ 4* LCD Rider Information Center: User Selectable Red Backlighting & Brightness, Programmable Service Intervals, Speedomi Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel G
Other Standard Features	Gas Assist Dump Box, Single Latch Tailgate, Rear-mounted Fiberglass Insulated Exhaust System, Standard In-dash SAE Charge Port, 575 CCA Battery, 660W Charging System (Stator)	Premium Cut & Sew Seats, Polaris Pulse Electrical System (3 position), Standard In-Dash SAE Charge Port.	Premium Cut & Sew Seats with Contoured Seatbacks and Embroidered Polaris Branding, Premium Steering Wheel and Interior Accents, Polaris Pulse Electrical System (Ringstron) Standard In-Pach SAF Charge Part NEC Front Badge	Polaris HD 4,500 Lb. Synthetic Rope Winch with Autostop and Wireless Ren Premium Pro-Shield Cab, Doors with Crank Windows, Fixed Glass Windshield

Ghost Gray

RANGER[®]











PELARIS Think Outside

www.polarisaustralia.com

O /polarisorv_aus

f / Polaris Australia

f / TeamRZR

Polaris reserves the right to withdraw any product from sale or change specifications and pricing without notice. Confirm model specifications and availability with your Polaris Dealer prior to ordering. The Polaris range is not intended for and may not be registered for on-road use. All competitive comparisons are based on published manufacturer specifications available at December 2022 unless otherwise specified. See other manufacturers for latest specifications. All photography taken with professional riders and drivers. For your safety, always operate Polaris products as instructed in the product manual and on warning labels. Never carry passengers on any product not designed for such use. Preserve your future riding opportunities by showing respect for the environment, local laws and the rights of others. Avoid excessive speeds and be particularly careful on difficult terrain. ©Polaris Sales Australia Pty Ltd ABN 62 088 081 949, Registered Office: 36 Grimes Court, Derrimut, VIC 3026. Printed December 2022.